



# SYSTEMS QJS

Project: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Location: \_\_\_\_\_

Contact/Phone: \_\_\_\_\_

### CT4 4 Foot QJS Track



#### PRODUCT DESCRIPTION

Rigid tubular aluminum low voltage track. 25 amp max. 300W @ 12Volts, 600W @ 24Volts. Includes track cover and end caps.  
**48" Length 1" Diameter**

#### ORDERING INFORMATION

Model	Hardware Finish	Example
CT4	BLK	CT4-BLK
	BLK Black	
	WHT White	

### CT8 8 Foot QJS Track



#### PRODUCT DESCRIPTION

Rigid tubular aluminum low voltage track. 25 amp max. 300W @ 12Volts, 600W @ 24Volts. Includes track cover and end caps.  
**96" Length 1" Diameter**

#### ORDERING INFORMATION

Model	Hardware Finish	Example
CT8	BLK	CT8-BLK
	BLK Black	
	WHT White	

### CTE01 Quick Jack Fixture Adapter



#### PRODUCT DESCRIPTION

Mounts all Alfa Quick Jack fixtures to the QJS Track. 75W max.  
**2 1/4" Length 3/4" Height**

#### ORDERING INFORMATION

Model	Hardware Finish	Example
CTE01	BLK	CTE01-BLK
	BLK Black	
	WHT White	

### CTJ01 QJS Track Mini-Connector- Conductive



#### PRODUCT DESCRIPTION

Mechanically and electrically joins two sections of QJS Track. 25 amp capacity. 300W @ 12V, 600W @ 24V.  
**1 3/4" Length**

#### ORDERING INFORMATION

Model	Hardware Finish	Example
CTJ01	BLK	CTJ01-BLK
	BLK Black	
	WHT White	

### CTJ02 QJS Track Mini-Connector- Non-Conductive



#### PRODUCT DESCRIPTION

Mechanically joins two sections of QJS Track.  
**1 3/4" Length**

#### ORDERING INFORMATION

Model	Hardware Finish	Example
CTJ02	BLK	CTJ02-BLK
	BLK Black	
	WHT White	

### CTJ03 QJS Track Flex-Connector- Conductive



#### PRODUCT DESCRIPTION

Joins two sections of QJS Track and flexes to various angles. 25 amp max. 300W @ 12Volts, 600W @ 24Volts.  
**12" Length 1" Diameter**

#### ORDERING INFORMATION

Model	Hardware Finish	Example
CTJ03	BLK	CTJ03-BLK
	BLK Black	
	WHT White	

### CTJ04 QJS Track "L" Connector



#### PRODUCT DESCRIPTION

Joins two sections of track at 90° angle. 25 amp max.  
300W @ 12Volts, 600W @ 24Volts.  
3" Length 1" Diameter

#### ORDERING INFORMATION

Model	Hardware Finish	Example
CTJ04	<b>BLK</b> BLK Black WHT White	CTJ04-BLK

### CTJ06 QJS Track Wall Mounts



#### PRODUCT DESCRIPTION

Allows wall mounting of QJS Track. Package of two.

#### ORDERING INFORMATION

Model	Hardware Finish	Example
CTJ06	<b>BLK</b> BLK Black WHT White	CTJ06-BLK

### CTJ08 QJS Track Supports



#### PRODUCT DESCRIPTION

Floats track 1/2" off of wall or ceiling. Package of two.

#### ORDERING INFORMATION

Model	Hardware Finish	Example
CTJ08	<b>BLK</b> BLK Black WHT White	CTJ08-BLK

### CTJ09 QJS Track Cable Support



#### PRODUCT DESCRIPTION

Complete with 6' 6" of aircraft cable, field cuttable. Consult factory for longer lengths.

#### ORDERING INFORMATION

Model	Hardware Finish	Example
CTJ09	<b>CHR</b> CHR Chrome STN Satin Nickel	CTJ09-CHR

### CTL01 QJS Track End Power Feed



#### PRODUCT DESCRIPTION

Used to supply power to the QJS Track System. 25 amp max.  
300W @ 12Volt, 600W @ 24Volt. Custom power feeds are available, consult factory.

2 1/2" Length 1" Diameter

#### ORDERING INFORMATION

Model	Hardware Finish	Example
CTL01	<b>BLK</b> BLK Black WHT White	CTL01-BLK

### 99170-12V QJS Track Surface Mount 12V 300W Magnetic Transformer



#### PRODUCT DESCRIPTION

Single or dual direct power feed capable. Includes de-buzzing coil. Equipped with 25A secondary breaker.  
120V input, 12V output.

8 1/2" Diameter 3 1/8" Height

#### ORDERING INFORMATION

Model	Hardware Finish	Example
99170-12V	<b>NKL</b> BLK Black NKL Nickel WHT White	99170-12V-NKL

**99170 24V QJS Track Surface Mount 600W Magnetic Transformer**



**PRODUCT DESCRIPTION**

Single or dual direct power feed capable. Equipped with 25A secondary breaker. 120V input, 24V output.

**8 1/2" Diameter 3 1/8" Height**

**ORDERING INFORMATION**

Model	Hardware Finish	Example
99170-24V	NKL	99170-24V-NKL
	BLK Black	
	NKL Nickel	
	WHT White	

**99150 12V 150W Remote Mount Magnetic Transformer**



**PRODUCT DESCRIPTION**

12-volt 150 watt single circuit magnetic transformer for remote mounting. Equipped with secondary breaker. 120V input, 12V output.

**10" Height 3 5/8" Width 4" Diameter**

**ORDERING INFORMATION**

Model	Example
99150	99150

**99106 12V 300W Remote Mount Magnetic Transformer**



**PRODUCT DESCRIPTION**

Equipped with 25A secondary breaker. Available with 277 VAC input. 120V input, 12V output.

**8 3/4" Length 4 1/4" Width 4" Height**

**ORDERING INFORMATION**

Model	Example
99106	99106
99106	
99106-277V-12	

**99106-PM 12V 300W Remote Mount Magnetic Transformer with Power Monitoring Protection**



**PRODUCT DESCRIPTION**

Option contains auto resetting short circuit and overload protection. 120V input, 12V output.

**6 1/2" Length 3 1/2" Width 3" Height**

**ORDERING INFORMATION**

Model	Example
99106-PM	99106-PM

**99107 12V 2 x 300W Remote Mount Magnetic Transformer**



**PRODUCT DESCRIPTION**

Dual 300W outputs. Equipped with 25A secondary breakers. Available with 277 VAC input. 120V input, 12V output.

**9 1/2" Length 4 1/2" Width 5" Height**

**ORDERING INFORMATION**

Model	Example
99107	99107
99107	
99107-277V-12	

**99107-PM 12V 2 x 300W Remote Mount Magnetic Transformer with Power Monitoring Protection**



**PRODUCT DESCRIPTION**

Dual 300W outputs. Option contains auto resetting short circuit and overload protection. 120V input, 12V output.

**7 1/4" Length 4 3/4" Width 4 1/4" Height**

**ORDERING INFORMATION**

Model	Example
99107-PM	99107-PM

**99116 24V 600W  
Remote Mount Magnetic  
Transformer**



**PRODUCT DESCRIPTION**

Equipped with 25A secondary breaker. 120V input, 24V output.

**9 1/2" Length 4 1/2" Width 5" Height**

**ORDERING INFORMATION**

Model	Example
99116	99116

**99117 24V 2 x 600W  
Remote Mount Magnetic  
Transformer**



**PRODUCT DESCRIPTION**

Dual 600W outputs. Equipped with 25A secondary breakers. 120V input, 24V output.

**10 1/2" Length 6" Width 5 1/2" Height**

**ORDERING INFORMATION**

Model	Example
99117	99117

**995 Secondary Wire**



**PRODUCT DESCRIPTION**

10 Gauge two conductor. High strand count reduces voltage drop. Alfa secondary wire is sold by the foot. Specify length when ordering. Example: 10' of 995 Secondary Wire is ordered as 10-995-BLK.

**ORDERING INFORMATION**

Model	Hardware Finish	Example
995	BLK	995-BLK
	BLK Black	
	CLR Clear	
	COP Copper	
	WHT White	