

Catalog Number
Notes
Type

FEATURES & SPECIFICATIONS

INTENDED USE — Provides general illumination for residential and commercial applications. Ideal for use as lighting in bathroom/lavatories, over hospital beds, hallways/corridors stairways and utility areas. **If required for commercial application or operation more than eight (8) hours per day, consult factory for available options.**

CONSTRUCTION — A distinctive contoured design complements a variety of decors. Durable milk-white acrylic diffuser provides a widespread uniform illumination. Suitable for vertical or horizontal mounting. Available in 2', 3' and 4' lengths.

OPTICS — Utilizes linear T8 fluorescent lamps for energy efficiency, superior color rendering and long life (not included).

ELECTRICAL — Standard with electronic ballast (120 volt, 60Hz) ensures no flickering and quiet operation without interfering with other electronics. Also available in other ballast configurations.

For use with non-dimmable switches only.

LISTINGS — UL listed to US and Canadian safety standard on Residential Electronic (RE) ballast fixtures and suitable for damp locations. For Non-RE ballast, UL and CSA (standard) for NOM Certified see options.

WARRANTY

2-year limited warranty. Complete warranty terms located at: www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Note: Actual performance may differ as a result of end-user environment and application.

Specifications subject to change without notice.

Indoor Decorative

Litepuff

VANITY

Linear T8 Fluorescent



DIMENSIONS						
Nominal size	Lamp configuration	Model number	Number of lamps	(A) Width inches (cm)	(B) Length inches (cm)	(C) Extension* inches (cm)
2'		11890	(2) 17W linear T8	5" (12.7)	27" (68.6)	4" (10.2)
3'		11891	(2) 25W linear T8	5" (12.7)	39" (99.1)	4" (10.2)
4'		11892	(2) 32W linear T8	5" (12.7)	51" (129.5)	4" (10.2)

*Extension from wall.
All dimensions are inches (centimeters) unless otherwise indicated.



ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: 11892RE

Series ^{1,2}	Residential ballast ³	Ballast/Voltage ⁴	Options
11890 2' - (2) 17W T8 fluorescent lamp required	RE 120 volt residential electronic ballast (standard)	(blank) RE ballast fixtures only	GEB Electronic ballast, <20%THD
11891 3' - (2) 25W T8 fluorescent lamps required	(blank) Other voltage and ballast types available (see ballast/voltage)	MVOLT Multi-volt	GEB10IS T8 electronic ballast, <10% THD, instant start
11892 4' - (2) 32W T8 fluorescent lamps required		120 120 Volt	GEB10PS T8 electronic ballast, 10% THD, program start
		277 277 Volt	NOM NOM Certified
		347 347 Volt	ACNS Advance Centium Series-Rapid Start
		Other voltage and ballast types (consult factory)	ADEZ Advance Mark X Dimming -Rapid Start
			ACNP Advance Centium-Instant Start
			APNP Advance-Rapid Start
			ADDE Advance Discreet -Instant Start
			ADOPR Advance Optanium-Rapid Start
			BINP NEMA Premium Normal Light Output-instant start
			BPHP NEMA Premium Normal Light Output-rapid start
			GEUSL GE; Ultrastart, High efficiency, Low output
			GEUM GE Ultra Max-Instant Start
			GEB10IS General Use Electronic-Instant Start
			GEB10PS Generic Electronic-Rapid Start
			OS10ISX Osram-Parallel Lamp Normal Light Output-Instant Start
			OS10ISXL Osram-Paralle Lamp Low Light Output-Instant Start
			TUBIHP Universal -Instant Start
			TUBPHP Universal-Program Start
			OS10PSX Osram QHE High Efficiency Normal Light Output Rapid Start
			(Consult factory for other options)

Replacement parts: Order as separate catalog number.

DVANPUFF 24	24" white acrylic diffuser
DVANPUFF 36	36" white acrylic diffuse
DVANPUFF 48	48" white acrylic diffuser

Notes

- Lamps not included.
- Use with non-dimmable switches only.
- Residential electronic ballast standard and requires RE designation.
- No designation for lamp type is required on RE ballast fixtures.

PHOTOMETRICS

Full photometric data report available within 2 weeks from request. Consult factory.