



1180L: 6" Fluorescent New Construction IC Airtight Housing



Dimensions:

| | |
|------------------|----------|
| Diameter: | 6 1/4" |
| Length: | 13 1/2" |
| Width: | 12 5/16" |
| Height: | 7 7/8" |

Features:

- Offers energy saving fluorescent lighting
- Meets Title 24 energy efficiency standards

Material List:

- 1 Housing - Steel / Aluminum - Undefined
- 1 Bulb - Frosted Glass - Undefined

Safety Listing:

Safety Listed for Damp Locations / IC

Instruction Sheets:

Bilingual (English - French) (HC-932FB)

Collection: Recessed Lighting

IC Airtight Fluorescent New Construction Recessed Housing.
Accommodates 26w Bulb

Trims: 1133AT, 1135, 1155AT, 1157AT, 1160AT, 11061AT, 11063AT

Airtight Construction: Meets airtight requirements for 2.0 CFM or less air leakage.

Adjustable Socket Plate: Adjustable socket plate assembly provides flexibility in lamping options and precise lamp placement with various trims.

Housing Adjustment: Housing adjusts vertically for various ceiling thicknesses.

Bar Hanger Locking Screw: Tighten screw to lock bar hangers in place.

Bar Hanger: Break-away bar hangers easily extend and will not fall out of plaster flange, providing sturdy installation.

Independently Tested Ballast: Provided with integral ballast offering years of trouble-free operation.

Junction Box with Integral Romex Connector: Junction box with integral romex connector, quick-push and lock connector and through circuit wiring with 4 in, 4 out #12 wire, saves installation time.

Safe - Thermally Protected/Listed for Damp Location: IC housing is approved for use in direct contact with insulation.

Tab to locate on bottom of joist

[26w PL Triple Twin Lamp with G241-3 Base: 97046](#)

UPC #:785652204593

Finish: Undefined ()

Shipping Information:

| Package Type | Product # | Quantity | UPC | Length | Width | Height | Cube | Weight | Fr. Class | UPS Ship |
|--------------|-----------|----------|----------------|--------|-------|--------|--------|--------|-----------|----------|
| Individual | 1180L | 1 | 785652204593 | 14 | 10.5 | 8 | 0.681 | 2.9 | 100 | Yes |
| Master Pack | 1180L | 6 | 10785652204590 | 24.5 | 21 | 8.75 | 2.605 | 20.8 | 100 | Yes |
| NJ Pallet | | 192 | | 48 | 40 | 76 | 84.444 | 665.6 | | No |
| NV Pallet | | 192 | | 48 | 40 | 75 | 83.333 | 672 | | No |

Trim



11061AT-172
RECESSED TRIM
Antique Bronze - White Aluminum
Baffle
White Aluminum Trim
Maximum Wattage:
26w 4-Pin



11061AT-861
RECESSED TRIM
Satin Nickel - White Aluminum
Baffle
White Aluminum Trim
Maximum Wattage:
26w 4-Pin



11063AT-15
RECESSED TRIM
White Steel Housing
White Steel Trim
Maximum Wattage:
26w 4-Pin



11233AT-15
RECESSED TRIM
Satin White Glass
Diffuser
White Aluminum
Reflector
White Aluminum Trim
Maximum Wattage:
26w 4-Pin
Suitable For Shower
Light



11235AT-15
RECESSED TRIM
Steel Trim
Maximum Wattage:
26w 4-Pin



11255AT-15
RECESSED TRIM
Aluminum Trim
Maximum Wattage:
26w 4-Pin
Suitable For Shower Light



1157AT-14
6" Deep Cone Baffle Trim
White Trim / Baffle Aluminum
Baffle
White Trim / Baffle Aluminum
Trim
Maximum Wattage:
26w 4-Pin



1157AT-15
**6" Deep Cone Baffle
Trim**
Black Aluminum Baffle
White Aluminum Trim
Maximum Wattage:
26w 4-Pin



1160AT-14
6" Deep Cone Multiplier T
White Trim / Baffle Aluminum
Reflector
White Trim / Baffle Aluminum Trim
Maximum Wattage:
26w 4-Pin



1160AT-22
6" Deep Cone Multiplier T
Polished Aluminum Aluminum
Reflector
White Aluminum Trim
Maximum Wattage:
26w 4-Pin