


# Rigid Standoff

## STANDOFF



Shown approximately 30% actual size.



tiella\_rigid\_standoff\_spec.pdf

## DESCRIPTION

The field-cutttable rigid standoff is recommended for curvy runs or runs with heavier elements, such as glass pendants. Rigid standoffs are compatible with various power feed options: use the chart below to determine the appropriate standoff for your run.

## FINISH

Bronze, Satin Nickel.

## WEIGHT

0.06-0.25 lb./0.03-0.11 kg. ±

## COMPATIBLE STANDOFF

LENGTH	USED WITH
2" (1.5")*	- Remote transformer with canopy - Recessed can transformer
3" (3.5")*	- Surface transformer 150w
4" (4.5")*	- Surface transformer 300w
5" (5.5")*	- Surface transformer 300w
6"	- Canopy or Surface tran. with 6" power extender
12"*	- Canopy or Surface tran. with 12" power extender
24"*	- Canopy or Surface tran. with 24" power extender
36"*	- Canopy or Surface tran. with 36" power extender
48"*	- Canopy or Surface tran. with 48" power extender
96"*	- Canopy or Surface tran. with 96" power extender

\*Actual length from ceiling to top of Rail.

## ORDERING INFORMATION

800RLS	LENGTH (A)	FINISH
02	2" (1.5")	Z Bronze
03	3" (3.5")	S Satin Nickel
04	4" (4.5")	
05	5" (5.5")	
06	6"	
12	12"	
24	24"	
36	36"	
48	48"	
96	96"	

800RLS \_\_\_\_\_

FIXTURE TYPE: \_\_\_\_\_

JOB NAME: \_\_\_\_\_

**tiella**  
real light, real simple

7400 Linder Avenue T 847.410.4400  
Skokie, Illinois 60077 F 847.410.4500  
[www.tiella.com](http://www.tiella.com)