


Product Specifications Report



Job Name:		Job Type:	
Comments:		Quantity:	
Product Number: 1109		Dimensions:	
 <p>1109 - Recessed Housing</p> <p>Single IC Sloped Recessed Light Housing, Adjustable to Fit Varied Ceilings. All housings are thermally protected and UL listed for damp location. This item accommodates up to 75w PAR 38 or 65w BR40 reflector lamp. Easy to install.</p> <p>Single IC Sloped Recessed Light Housing, Adjustable to Fit Varied Ceilings. All housings are thermally protected and UL listed for damp location. This item accommodates up to 75w PAR 38 or 65w BR40 reflector lamp. Easy to install features include junction box with integral Romex connector, breakaway flange, integral captive nail, and adjustable socket plate.</p> <p>75w PAR38 or 65w BR40</p> <p>Bar Hanger Locking Screw: Tighten screw to lock bar hangers in place.</p> <p>Bar Hanger: Break-away bar hangers easily extend and will not fall out of plaster flange, providing sturdy installation.</p> <p>Housing Adjustment: Housing adjusts vertically for various ceiling thicknesses.</p> <p>Junction Box with Integral Romex Connector: Junction box with integral romex connector, quick-push and lock connector and through circuit wiring with 4 in, 4 out #12 wire, saves installation time.</p> <p>Quick Hit: Integral captive nails included and positioned for fast, easy installation.</p> <p>Adjustable Socket Plate: Adjustable socket assembly provides flexibility in lamping options and precise lamp placement with various trims.</p> <p>Safe- Thermally Protected/Listed for Damp Location: IC housing is approved for use in direct contact with insulation.</p> <p>Safe Listed: Listed for use where insulation is kept at least 3" away from housing.</p> <p>UPC #: 785652110900 Product Type: Recessed Light</p>		Diameter: 6 3/8"	Switch Type: N/A
		Length: 14 1/8"	Mounting Proc.: Other
		Width: 13 1/2"	
		Height: 7 3/8"	
		Material List:	
Safety Listing:		cUL Listed for Damp Locations / IC UL Listed for Damp Locations / IC	
Instruction Sheets		English (HC-430)	

Trim



1121-14

Single-Light Recessed Inc

White Trim / Baffle Aluminum Baffle
 White Trim / Baffle Plastic Trim
 Maximum Wattage:
 75w Par38



1121-15

Single-Light Recessed Inc

Black Aluminum Baffle
 White Plastic Trim
 Maximum Wattage:
 75w Par38



1122-14

Single-Light Incandescent

White Trim / Baffle Plastic Baffle
 White Trim / Baffle Plastic Trim
 Maximum Wattage:
 75w Par38



1122-19

Single-Light Incandescent

Metallic Gold Plastic Baffle
 White Plastic Trim
 Maximum Wattage:
 75w Par38



1122-22

Single-Light Incandescent

Polished Aluminum Plastic Baffle
 White Plastic Trim
 Maximum Wattage:
 75w Par38

Shipping Information

Package Type	Quantity	UPC	Length	Width	Height	Cube	Weight	UPS Ship	Label
Individual	1	785652110900	14.5	14.5	7.75	0.943	3.1	Yes	
Master Pack	6	10785652110907	24.25	24.25	9	3.063	22.3	Yes	A M-1
NJ Pallet	120		48	40	72	80	446	No	
NV Pallet	120		48	40	72	80	446	No	