

Product Specifications Report



Job Name:		Job Type:	
Comments:		Quantity:	
Product Number: 1128FB		Dimensions:	
		Length: 25 1/2"	Mounting Proc.: Other
		Width: 17 1/2"	
		Height: 9 3/4"	
		Material List:	
		1 Body - Steel -	
		Instruction Sheets	
		English (HC-972)	

1128FB - Fire Barrier Recessed Housing

IC Airtight 6" Fire Barrier Housing

Sea Gull Lighting's Fire barrier lighting products are designed specifically for residential and commercial applications that require floor/ceilings to be one hour fire-rated.

One recessed housing replaces the traditional field installed, fire resistant drywall fire barrier, simplifying the approval process for building inspectors, plus, the easy to install design reduces installation cost, time and the number of required subcontractors. Ideal for multi-family dwellings such as apartment buildings, assisted living communities, and medical facilities.

Features four knockouts for wiring flexibility.

Easy to install with four screws.

Heavy 24 gauge galvanized steel enclosure.

Patent pending design.

Secure to framing prior to drywall.

Maximum two fixtures within 36 sq. ft. area

Minimum O.C. fixture spacing of 24" within same truss cavity.

Minimum C.T.C. fixture spacing of 34" for adjacent truss cavity.

Meets commercial building code safety standards for barriers.

Replaces the need for time consuming construction barriers on the job site.

Uses same trim selection as 1128.

Meets following fire-rated specifications: UL263, UBC 7-1, NFPA 251, and ASI A2.1.

Safe- Thermally Protected/Listed for Damp Location: IC housing is approved for use in direct contact with insulation.

Airtight Construction: Meets airtight requirements for 2.0 CFM or less air leakage.

Housing Adjustment: Housing adjusts vertically for various ceiling thicknesses.

Adjustable socket assembly provides flexibility in lamping options and precise lamp placement with various trims.

Junction Box with Integral Romex Connector: Junction box with integral romex connector, quick-push and lock connector and through circuit wiring with 4 in, 4 out #12 wire, saves installation time.

Bar Hanger Locking Screws: Tighten screws to lock bar hangers in place.

One hour-rated fire barrier certified to ASTM E-119.

UPC #: 785652011207

Product Type: Recessed
Light

Trim



1120-15

Single-Light Recessed Inc

White Steel Trim
 Maximum Wattage:
 75w Par30L
 65w BR-30



1125-14

Single-Light Incandescent

White Trim / Baffle Aluminum Baffle
 White Trim / Baffle Aluminum Trim
 Maximum Wattage:
 65w BR-30
 50w Par30S
 75w Par30L



1126-14

Single-Light Incandescent

White Trim / Baffle Steel Baffle
 White Trim / Baffle Steel Trim
 Maximum Wattage:
 50w Par30S
 75w Par30L
 65w BR-30



1126-15

Single-Light Incandescent

Black Steel Baffle
 White Steel Trim
 Maximum Wattage:
 50w Par30S
 75w Par30L
 65w BR-30



1133AT-15

Recessed Trim

White Glass Diffuser
 White Plastic Trim
 Maximum Wattage:
 40w A-19
 Suitable For Shower Light



1134-68

Single-Light Incandescent

White Plastic Plastic Diffuser
 White Plastic Trim
 Maximum Wattage:
 40w A-19
 Suitable For Shower Light



1135AT-15

6" Flat Glass Trim

Smooth White Glass Diffuser
 White Steel Trim
 Maximum Wattage:
 40w A-19



1136-15

Single-Light Incandescent

White
 White Steel Trim
 Maximum Wattage:
 75w Par30L
 65w BR-30



1136AT-15

6" Eyeball Trim

White
 White Steel Trim
 Maximum Wattage:
 75w Par30L
 65w BR-30



1151-14

Single-Light Incandescent

White Aluminum Trim
 Maximum Wattage:
 90w Par38
 65w BR-30
 50w Par30S
 75w Par30L



1151-15

Single-Light Incandescent

Black Aluminum Baffle
 White Aluminum Trim
 Maximum Wattage:
 90w Par38
 65w BR-30
 50w Par30S
 75w Par30L



1151AT-14

6" Baffle Trim

White Trim / Baffle Aluminum Trim
 Maximum Wattage:
 50w Par30S
 75w Par30L
 90w Par38
 65w BR-30



1151AT-15

6" Baffle Trim

Black Aluminum Baffle
 White Aluminum Trim
 Maximum Wattage:
 90w Par38
 65w BR-30
 50w Par30S



1154-14

Single-Light Incandescent

White Trim / Baffle Aluminum Baffle
 White Trim / Baffle Aluminum Trim
 Maximum Wattage:
 50w Par30S



1154AT-14

6" Open Cone Shower Trim

White Trim / Baffle Aluminum Baffle
 White Trim / Baffle Aluminum Trim
 Maximum Wattage:
 50w Par30S



1155AT-15

White Recessed Trim

Clear Glass Glass
 White Aluminum Trim
 Maximum Wattage:
 40w A-19
 Suitable For Shower Light

70W PAR38	70W PAR38 90w Par38 Suitable For Shower Light	70W PAR38 90w Par38 Suitable For Shower Light
-----------	---	---

Shipping Information									
Package Type	Quantity	UPC	Length	Width	Height	Cube	Weight	UPS Ship	Label
Individual	1	785652011207	25.5	17.75	11.75	3.078	15.2	Yes	1 A-1 IP
NJ Pallet	18		48	40	72	80	273.6	No	
NV Pallet	18		48	40	72	80	273.6	No	