


Product Specifications Report



Job Name:		Job Type:	
Comments:		Quantity:	
Product Number: 1177LE		Dimensions:	
 <p>1177LE - Fluorescent IC Airtight Housing</p> <p>New construction fluorescent recessed lighting. UL listed for damp location with one class P HPF Electronic ballast. Bar hanger adjustable to 24". Shown with 1132-22 trim (sold separately).</p> <p>IC Airtight Fluorescent New Construction Recessed Housing.</p> <p>Electronic Ballast; (Ref. Dim. 1128); uses trims 1132-14,1132-19,1132-22,1126-14,1126-15,1133-15,1135-02,1135-15.</p> <p>Airtight Construction: Meets airtight requirements for 2.0 CFM or less air leakage.</p> <p>Adjustable Socket Plate: Adjustable socket assembly provides flexibility in lamping options and precise lamp placement with various trims.</p> <p>Housing Adjustment: Housing adjusts vertically for various ceiling thicknesses.</p> <p>Bar Hanger: Break-away bar hangers easily extend and will not fall out of plaster flange, providing sturdy installation.</p> <p>Quick Hit: Integral captive nails included and positioned for fast, easy installation.</p> <p>Bar Hanger Locking Screw: Tighten screw to lock bar hangers in place.</p> <p>Trouble-Free Ballast: Provided with integral ballast offering years of trouble-free operation.</p> <p>Junction Box with Integral Romex Connector: Junction box with integral romex connector, quick-push and lock connector and through circuit wiring with 4 in, 4 out #12 wire, saves installation time.</p> <p>Safe- Thermally Protected/Listed for Damp Location: IC housing is approved for use in direct contact with insulation.</p> <p>UPC #: 785652011771 Product Type: Recessed Light</p>		<p>Diameter: 6 1/4" Switch Type: N/A</p> <p>Length: 13 1/2" Mounting Proc.: Other</p> <p>Width: 12 5/16"</p> <p>Height: 7 7/8"</p>	
		Material List:	
		1 Housing - Steel/Aluminum -	
		Safety Listing:	
		cUL Listed for Damp Locations / IC UL Listed for Damp Locations / IC	
Instruction Sheets			
English (HC-932)			
Features:			
Energy Star Compliant	Fluorescent		
Title 24			

Trim



11061AT-172

6" Deep Cone Multiplier T

Antique Bronze - White Aluminum
 Baffle
 White Aluminum Trim
 Maximum Wattage:
 26w 4 - Pin



11061AT-861

6" Deep Cone Multiplier T

Satin Nickel - White Aluminum
 Baffle
 White Aluminum Trim
 Maximum Wattage:
 26w 4 - Pin



11063AT-15

6" Wall Wash Trim

White Steel Housing
 White Steel Trim
 Maximum Wattage:
 26w 4 - Pin



11233AT-15

6" Shower Trim

Satin White Glass
 Diffuser
 White Aluminum
 Reflector
 White Aluminum Trim
 Maximum Wattage:
 26w 4 - Pin
 Suitable For Shower
 Light



11235AT-15

6" Flat Glass Trim

Steel Trim
 Maximum Wattage:
 26w 4 - Pin



11255AT-15

6" Shower Trim

Aluminum Trim
 Maximum Wattage:
 26w 4 - Pin
 Suitable For Shower Light



1157AT-14

White Recessed Trim

White Trim / Baffle Aluminum
 Baffle
 White Trim / Baffle Aluminum
 Trim
 Maximum Wattage:
 26w 4 - Pin



1157AT-15

6" Deep Cone Baffle Trim

Black Aluminum Baffle
 White Aluminum Trim
 Maximum Wattage:
 26w 4 - Pin



1160AT-14

White Recessed Trim

White Trim / Baffle Aluminum
 Reflector
 White Trim / Baffle Aluminum
 Trim
 Maximum Wattage:
 26w 4 - Pin



1160AT-22

6" Deep Cone Multiplier T

Polished Aluminum Aluminum
 Reflector
 White Aluminum Trim
 Maximum Wattage:
 26w 4 - Pin

Shipping Information

Package Type	Quantity	UPC	Length	Width	Height	Cube	Weight	UPS Ship	Label
Individual	1	785652011771	15.5	9	8	0.646	3.75	Yes	19 E-6 IP
Master Pack	6	10785652011778	26	18.5	9	2.505	25.2	Yes	17 E-2 M
NJ Pallet	144		48	40	72	80	604.8	No	
NV Pallet	144		48	40	72	80	604.8	No	