Product Specifications Report



Job Name:	Job Type:
Comments:	Quantity:

Product Number: 1179



1179 - Recessed IC-Airtight Housing

4 Inch Line Voltage New Construction Airtight IC Rated Recessed Housing

Airtight Construction: Meets airtight requirements for 2.0 CFM or less air leakage.

Inner Housing: Double wall aluminum construction helps dissipate heat. The inner housing can be adjusted in the plaster frame to compensate for various ceiling thicknesses.

Socket: Fixed position porcelain socket with nickel plated brass screw shell provides consistent lamp positioning.

Quick Hit: Integral captive nails included and positioned for fast, easy installation.

Plaster Frame: Galvanized and steel construction. The housing can be removed from the plaster frame to provide access to the junction box. Plaster frame includes locking screws for hanger bars and cutouts for crimping hanger bars in position.

Bar Hanger: Break-away bar hangers easily extend and will not fall out of plaster flange, providing sturdy installation.

Listed for through branch circuit wiring. Positioned to accommodate straight conduct runs. Seven conduit knockouts are uniform 1/2" size with true pryout slots. Four Romex pryouts with integral strain relief also included.

Outer Housing: Aluminum construction helps dissipate heat.

UPC #: 785652117909 Product Type: Recessed

Light

Dimensions:

Diameter: 4 5/16" Switch Type: N/A

Length: 13 7/16" Mounting Proc.: Other

Width: 8 1/4"

Height: 5 13/16"

Material List:

1 Housing - Steel -

Saftey Listing:

cUL Listed for Damp Locations UL Listed for Damp Locations

Instruction Sheets

English (HC-1035)

Trim



11090AT-15

4" Pin Hole Trim

White Aluminum Reflector White Steel Trim Maximum Wattage: 35w Par20



11091AT-15

4" Wall Wash Trim

White Steel Baffle White Aluminum Reflector White Steel Trim Maximum Wattage: 35w Par20



11092AT-15

4" Shower Trim

Frosted Glass Glass White Aluminum Reflector White Aluminum Trim Maximum Wattage: 35w Par20 Suitable For Shower Light



11094AT-14

4"pen Shower Trim

White Trim / Baffle Aluminum Trim Maximum Wattage: 50w Par20 Suitable For Shower Light



1152AT-15

Recessed Trim

Frosted Glass Glass Polished Aluminum Aluminum Reflector White Steel Trim Maximum Wattage: 35w Par20 Suitable For Shower Light



1153AT-15

Recessed Trim

Clear Glass Glass Polished Aluminum Aluminum Reflector White Steel Trim Maximum Wattage: 35w Par20 Suitable For Shower Light



1156AT-14

Recessed Trim

White Trim / Baffle Steel Baffle White Steel Trim Maximum Wattage: 50w Par20



1156AT-15

Recessed Trim

Black Steel Baffle White Steel Trim Maximum Wattage: 50w Par20



1162AT-14

Recessed Trim

White Trim / Baffle Aluminum Aluminum Multiplier White Aluminum Trim Maximum Wattage: 50w Par20



1162AT-172

4" Multiplier Trim

Antique Bronze - White Aluminum Reflector White Steel Trim Maximum Wattage: 50w Par20



1162AT-19

Recessed Trim

Metallic Gold Aluminum Baffle White Aluminum Trim Maximum Wattage: 50w Par20



1162AT-22

Recessed Trim

Polished Aluminum Aluminum Baffle White Aluminum Trim Maximum Wattage: 50w Par20



1162AT-71

4" Multiplier Trim

Antique Bronze Aluminum Reflector Antique Bronze Steel Trim Maximum Wattage: 50w Par20



1162AT-849

4" Multiplier Trim

Satin Nickel Aluminum Reflector Satin Nickel Steel Trim Maximum Wattage: 50w Par20



1162AT-861

4" Multiplier Trim

Satin Nickel - White Aluminum Reflector White Steel Trim Maximum Wattage: 50w Par20



1166AT-15

Single-Light Recessed Tri

White Steel Housing White Steel Trim Maximum Wattage: 50w Par20

Package Type	Quantity	UPC	Length	Width	Height	Cube	Weight	UPS Ship	Label
Individual	1	785652117909	8.5	6	5.38	0.159	1.71	Yes	A IP-1
Master Pack	6	10785652117906	22	17.75	7	1.582	16.32	Yes	A M-1
NJ Pallet	240		48	40	74.25	82.5	594	No	
NV Pallet	120		48	40	75	83.333	326.4	No	