

# Spree

## ARCHITECTURAL HEAD



SPREE

Shown approximately 25% actual size.

### DESCRIPTION

Compact flood, rotates 350° around the stem; pivots 345°.

### SYSTEM

Available for FreeJack, MonoRail, Two-Circuit MonoRail, and Wall MonoRail. For use on T-trak, order FreeJack version and T-trak FreeJack Connector (sold separately).

### COLOR

None.

### FINISH

Chrome, satin nickel.

### LAMP


Low-voltage 50 watt Halogen bi-pin lamp (included).

### ACCESSORIES AND OPTICAL CONTROLS

None.

### WEIGHT

0.30 lb./0.13 kg. ±



Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system.

### ORDERING INFORMATION

700	SYSTEM	SPR	LENGTH (A)	FINISH	VOLTAGE
	FJ	FREEJACK	03 3"	C CHROME	12 VOLT
	MO	MONORAIL	06 6"	S SATIN NICKEL	24 24 VOLT
	MO2	TWO-CIRCUIT MONORAIL	12 12"		
			18 18"		
	WMO	WALL MONORAIL	24 24"		



**TECH LIGHTING®**

7400 Linder Avenue T 847.410.4400  
 Skokie, Illinois 60077 F 847.410.4500

[www.techlighting.com](http://www.techlighting.com)

700 \_\_\_\_\_ SPR \_\_\_\_\_

FIXTURE TYPE: \_\_\_\_\_

JOB NAME: \_\_\_\_\_

